



Interrupteurs différentiels

Tétrapolaires

30 MA **300 MA**

- Protection différentielle
- Bornes alignées 25 mm²
- In de 40 à 100 A
- Un 230/400 V~50/60Hz
- Type A - AC - B - G
- I_{Δn} 30 et 300 mA
- I_{Δc} 10000 A
- Norme EN 61008-1



Fiche technique
téléchargeable sur le site



TERTIAIRE &
INDUSTRIE

NOUVEAU !

	Calibre	Type AC	Type A	Type B	Type G	Module	Emballage
30 mA	40 A	03432	03442	03472	03446	4	1
	63 A	03434	03444	03474	03448	4	1
	80 A	03436	-	-	-	4	1
	100 A	03438	-	-	-	4	1
300 mA	40 A	03462	-	-	-	4	1
	63 A	03464	-	-	-	4	1
	80 A	03466	-	-	-	4	1
	100 A	03468	-	-	-	4	1

ACCESSOIRES



06152



06162



06008



06052

Référence	Description	Emballage
06052	Kit d'alimentation 63 A ID4 / 12DPN	1
06156	Peigne tétrapolaire 63 A ID4 / 2 tétra	1
06152	Peigne tétrapolaire 63 A (1 m)	1 m
06162	Peigne tétrapolaire 63 A à fourche	1 m
06010	Connecteur 25 mm ²	20
06008	Connecteur 25 mm ² à fourche	20